



SWIGER COIL SYSTEMS, LLC.  
 4625 MANUFACTURING RD.  
 CLEVELAND, OH 44135  
 TOLL FREE: 1 800-321-3310  
 216-362-7500  
 FAX: 216-362-0999  
 www.swigercoil.com

# A.C. STATOR DATA

## SCS SPEC: \_\_\_\_\_

CUSTOMER		MFG.		FRAME	
DATA BY		HP		SERIAL	
DATE		KW		TYPE	
PHONE		RPM		RISE	
FAX NO.		VOLTS		MOTOR APPL.	
P.O. NO.		AMPS		HZ	PH.

1. Core bore	1	21. Op. conn. End extension	21	
2. Core length	2	22. Small drop (Req'd if 7 is No)	22	
3. Finger plate width	3	23. Large drop (Req'd if 7 is No)	23	
4. vents: Qty:	Width:	24. NO. of slots/coils	24	
5. Back Iron	5	25. Coil throw slots 1 &	25	
6. Average tooth width	6	26. Turns per coil	26	
7. Coil supports Yes No	7	27. Wires in parallel	Wide	High
8. Conn. Supports ring from core	8	28. Wire sizes	28A	X
9. Conn. Supports ring I.D.	9		28B	X
10. Op. Conn. Support ring from core	10	29. Strand insulation (as found)	29	
11. Op. Conn. Support ring I.D.	11	30. Weight per coil	lbs.	
12. Clearance coil-baffle (Conn.)	12	31. Jumpers (circle)	1-4	1-7
13. Clearance coil-baffle (op. Conn.)	13	32. Connection (circle)	Star	Delta
14. Total slot depth	14	33. Number of circuits		
15. Slot depth under wedge	15	34. Coil grouping		
16. Slot width	16	35. Iron Skew Amount	Left	Right
17. Overall coil length	17	Leads	Sleeved	Taped
18. Top straight length	18	Corona shield	Yes	No
19. Bottom straight length	19	36. Insulation class req'd (circle)		
20. Conn. End extension	20	V.P.I	Dip & bake	Hermetic
Winding Requirements		F	H	Sealed System
Liner to be used: Yes No	Thickness:	SPECIAL INSTRUCTIONS:		
Complete wdg. Sup.	SLOT FILLERS ONLY			
Wedges: Yes No				
Tin Leads: Yes No				

